

# Superreel® - Industrial Reel

## 2 inch hose reel

2 inch hose reel, spring retractable, Gear-driven crank rewind, or chain and sprocket drive powered by an electric, hydraulic or compressed air motor.

90° ball bearing swivel joint with 2 inch victaulic. Flanged riser with 2 inch female NPT threads. Other sizes and/or threads can be furnished and must be specified. Temperatures from -20° F to +225° F (-29° C to +107° C). Consult factory for other pressures & temps. And we offer special products beyond 2 inch. Specify height, width and depth dimensions to fit your space requirement. Shipped completely assembled, ready to install.

## OUR CAPABILITIES

- Ultra-high pressure and high current, the highest pressure of gas and liquid up to 80-100MPA. Taking advantage of the National New Energy Policy, the maximum current of the DC charging reel can reach to 500A.
- Super-long. Spring-driven reels can handle hoses or cables up to 50 meters. Motor-driven reels' capacity up to 3000 meters.
- Engineering reciprocation. One of the few domestic manufacturers that can produce reciprocating hose reels and multi-line hydraulic reels.
- Smart reels with intelligent functions. Limit, feedback, measurement, remote control, APP control, adaptive control and other functions are used in our reels.
- Hose and cable combined reels. One reel can manage/ transmit media including acousto-optic signals, various gas-liquid media, etc, at the same time.



# Superreel® - Industrial Reel

---

